


Out of Darkness

Helping the blind see with artificial vision.



Visual impairment is a major disability faced by millions around the world. Right now, the only way to gain information about the world, reading, and enjoy life, and thus, that of sight can convey restrict one's professional advancement and social interaction. Recently, several groups around the world have used prototype of artificial vision systems based on the principle of electrical activation of the retina (1). The retina is composed of multiple layers of neurons (2). Microstimulation, electrically activate neurons, electrically stimulate the retina neurons that are sensitive to light. When photoreceptors are attacked by disease, the eye loses the ability to sense light. Current research focuses on how to replace the photoreceptors. However, they can't be replaced by electrical pulses. Thus, an implantable retinal stimulator can produce the sensation of light in a blind person. These systems typically consist of an image sensor, integrated circuits to generate stimulation pulses, packaging to protect the implanted

circuits, and a flexible, low-profile microelectrode array, which is implanted directly to apply an electrical stimulus (3). Figure 1. Current prototype systems all have several components that are sensitive to the light, including image sensor, camera, inductive energy transfer system to wireless power the system, and data collection hardware to allow wireless programming of the system to wireless power the system, and data collection hardware to allow wireless programming of the system. In this regard, several groups have demonstrated increased mobility and improved performance in visually impaired tasks. Current researchers are the subject of this that can be aided by active implants, so low power systems are needed to power the system. Early implantable devices have a high-power battery. Power is provided by external coil can change or technology, then low power is available for retina stimulation. The external system can supply low power technology to manage power usage to that the patient does not need to carry a large battery. Gene Hirasaki has worked with our team for more than 12 years to develop the prosthetic technology with these instruments (1) that could benefit retina prostheses. (1) low power digital image processing circuit could be the external visual processing unit of Second Sight Medical

Figure 1: Schematic diagram of an external camera, transmitter, and internal microelectrode array. (1) low power digital image processing circuit could be the external visual processing unit of Second Sight Medical




Figure 1: Schematic diagram of an external camera, transmitter, and internal microelectrode array. (1) low power digital image processing circuit could be the external visual processing unit of Second Sight Medical

Several groups around the world have tested prototypes of artificial vision systems based on the principle of electrical activation of the retina.

Products Argus II Retinal Prosthesis, which was recently approved for sale in Europe. Research collaborations between the University of Southern California (USC) and the University of Southern California (USC) have also resulted in advanced technology for future biomedical products, including the development of an implantable camera to replace the external camera and provide for the natural coupling of head and eye movements (4). Current microelectrode technology is limited in activating the retina, which necessitates a continuous external power supply, which an implanted battery would not have the necessary capacity to power an implant without frequent recharging. Future objectives in microelectrode array technology are to achieve closer contact between the implant and the retina, which may reduce stimulation power requirements to below 1 mW while it is somewhat speculative to assume that such microelectrode development will occur. It is nevertheless important to consider the possibility of a fully implantable, self-sustaining, microelectrode prosthesis, which a device would approach the "bionic eye" envisioned in popular culture (5). The Jay Walker Center team at USC, however, external power sources are abundant in the eye. Incident light, eye motion, and thermal gradients can all be converted to electricity for signal generation. With such a system, an even greater challenge is to extract low power, or close to zero, in the retina when the imaging optics, image sensor,

44 SPRING 2011 // IEEE SIGNAL PROCESSING MAGAZINE

نوشته شده توسط دکتر اصلانزاده

دوشنبه, 09 مرداد 1391 04:24 - آخرین به روز رسانی شنبه, 29 تیر 1392 14:20

image processor, and simulate circuits as well as design the eye. The eye is functionally required by color and movement, and the hand is able to see. This goal is the focus of the Neuro-Optic electronic systems course at USC, as well as an increasing number of academic and industrial projects around the world. Continued development of low power microelectronics will give a critical role in the success of this computer of the worthwhile endeavor.

References

1. J. S. Brannan and M. S. Sherrington, "Visual Systems: The Eye and Brain," Cambridge University Press, 2000.
2. H. H. Sliney, "The Eye and Brain," Cambridge University Press, 2000.
3. R. S. Berchiazzi, "The Eye and Brain," Cambridge University Press, 2000.
4. J. S. Brannan and M. S. Sherrington, "Visual Systems: The Eye and Brain," Cambridge University Press, 2000.
5. H. H. Sliney, "The Eye and Brain," Cambridge University Press, 2000.
6. R. S. Berchiazzi, "The Eye and Brain," Cambridge University Press, 2000.
7. J. S. Brannan and M. S. Sherrington, "Visual Systems: The Eye and Brain," Cambridge University Press, 2000.
8. H. H. Sliney, "The Eye and Brain," Cambridge University Press, 2000.
9. R. S. Berchiazzi, "The Eye and Brain," Cambridge University Press, 2000.
10. J. S. Brannan and M. S. Sherrington, "Visual Systems: The Eye and Brain," Cambridge University Press, 2000.

Gene Fronts has worked with our team for over a decade, identifying low-power technology.

John F. Brannan is the Director of the USC Center for Neuro-Optic Engineering and is also the Director of the USC Center for Neuro-Optic Engineering. He is currently a professor of electrical engineering at USC. He has been a member of the USC Center for Neuro-Optic Engineering since its inception in 1985. He has been a member of the USC Center for Neuro-Optic Engineering since its inception in 1985. He has been a member of the USC Center for Neuro-Optic Engineering since its inception in 1985.

Mark S. Sherrington currently holds the position of Dean of the USC Center for Neuro-Optic Engineering and is also the Director of the USC Center for Neuro-Optic Engineering. He is currently a professor of electrical engineering at USC. He has been a member of the USC Center for Neuro-Optic Engineering since its inception in 1985. He has been a member of the USC Center for Neuro-Optic Engineering since its inception in 1985.

USC Center for Neuro-Optic Engineering // 2012-12-14