

Vision impairment is a major disability faced by millions around the world. Right now, eyes in direct contact with the world can convey visual information about the world, reading, and other tasks, and thus help the user to see the world. However, several groups around the world have used principles of artificial vision systems based on the principle of electrical activation of the retina (1). The retina is composed of multiple layers of neurons (2). In a natural eye, photoreceptors (3) receive their signals from the photoreceptors, however, can instead be activated by electrical pulses. Thus, an implantable artificial stimulator can produce the sensation of light in a blind person. These systems typically consist of an image sensor, integrated circuits to generate stimulation pulses, packaging to protect the implanted device, and a flexible, low-profile microelectronic array, which is implanted directly to apply an electrical stimulus to the retina. In lower-resolution devices (4), current prototype systems all have several components that are essential to the system, including image sensor, camera, interface, energy transfer system to wireless power the system, and data collection hardware to allow wireless programming of the system. In higher resolution devices, each device has demonstrated increased mobility and improved performance in visually guided tasks.

**James D. Weiland,
Mark S. Foxman, and
Armand K. Engager Jr.**

Several groups around the world have used principles of artificial vision systems based on the principle of electrical activation of the retina (1). The retina is composed of multiple layers of neurons (2). In a natural eye, photoreceptors (3) receive their signals from the photoreceptors, however, can instead be activated by electrical pulses. Thus, an implantable artificial stimulator can produce the sensation of light in a blind person. These systems typically consist of an image sensor, integrated circuits to generate stimulation pulses, packaging to protect the implanted device, and a flexible, low-profile microelectronic array, which is implanted directly to apply an electrical stimulus to the retina. In lower-resolution devices (4), current prototype systems all have several components that are essential to the system, including image sensor, camera, interface, energy transfer system to wireless power the system, and data collection hardware to allow wireless programming of the system. In higher resolution devices, each device has demonstrated increased mobility and improved performance in visually guided tasks.

Several groups around the world have used principles of artificial vision systems based on the principle of electrical activation of the retina (1). The retina is composed of multiple layers of neurons (2). In a natural eye, photoreceptors (3) receive their signals from the photoreceptors, however, can instead be activated by electrical pulses. Thus, an implantable artificial stimulator can produce the sensation of light in a blind person. These systems typically consist of an image sensor, integrated circuits to generate stimulation pulses, packaging to protect the implanted device, and a flexible, low-profile microelectronic array, which is implanted directly to apply an electrical stimulus to the retina. In lower-resolution devices (4), current prototype systems all have several components that are essential to the system, including image sensor, camera, interface, energy transfer system to wireless power the system, and data collection hardware to allow wireless programming of the system. In higher resolution devices, each device has demonstrated increased mobility and improved performance in visually guided tasks.




FIGURE 1. Schematic diagram of an artificial retina system, including an external microelectronic array that is implanted directly to the retina. Reproduced with permission from the Annual Review of Biomedical Engineering, Vol. 1 (2008) by Annual Reviews. www.annualreviews.org.

Several groups around the world have tested prototypes of artificial vision systems based on the principle of electrical activation of the retina.

Several groups around the world have tested prototypes of artificial vision systems based on the principle of electrical activation of the retina. These systems typically consist of an image sensor, integrated circuits to generate stimulation pulses, packaging to protect the implanted device, and a flexible, low-profile microelectronic array, which is implanted directly to apply an electrical stimulus to the retina. In lower-resolution devices (4), current prototype systems all have several components that are essential to the system, including image sensor, camera, interface, energy transfer system to wireless power the system, and data collection hardware to allow wireless programming of the system. In higher resolution devices, each device has demonstrated increased mobility and improved performance in visually guided tasks.

44 OPTICS 2013 | www.nature.com/naturephotonics

